


Wire Rope Thimbles to U.S. Federal Specification FF-T-276b Extra Heavy Duty, Hot Dipped Galvanized Finish





HG-3414

Rope Size (dia.)		Dimensions (mm)					Weight (kg)
(mm)	(in.)	A	B	C	D	E	
6-7	1/4"	56	41	38	22	10	0.003
8	5/16"	64	48	46	27	13	0.054
9-10	3/8"	73	54	54	28	16	0.098
11-12	7/16"	83	60	60	32	18	0.158
13-15	1/2" - 9/16"	92	70	70	38	23	0.232
16	5/8"	108	83	79	44	25	0.344
18-20	3/4"	127	95	97	51	31	0.719
22	7/8"	140	108	108	57	35	0.810
24-26	1"	155	114	121	64	40	1.427
28-32	1-1/8" - 1-1/4"	178	130	149	73	48	1.812
32-35	1-1/4" - 1-3/8"	231	165	173	89	57	4.027
35-38	1-3/8" - 1-1/2"	229	159	181	89	67	5.885
40-42	1-5/8"	286	203	206	102	76	7.727
44-46	1-3/4"	310	229	216	114	78	8.068
48-52	1-7/8" - 2"	384	305	264	152	86	12.614
54-58	2-1/4"	445	356	302	178	99	17.955

Wire Rope Clips to U.S. Federal Specifications FF-C-450 Forged Steel Body, Hot Dipped Galvanized Finish

Rope Size (dia.)		Dimensions (mm)								Weight (kg)
(mm)	(in.)	A	B	C	D	E	F	G	H	
6	1/4"	7.9	26.2	12.7	19.0	16.8	14.2	30.2	36.3	0.086
8	5/16"	9.7	35.1	19.0	22.4	18.5	17.5	33.3	42.2	0.127
9-10	3/8"	11.2	38.1	19.0	25.4	23.1	19.0	41.4	49.3	0.227
11	7/16"	12.7	47.8	25.4	30.2	28.7	22.4	48.5	57.9	0.353
12-13	1/2"	12.7	47.8	25.4	30.2	28.7	22.4	48.5	57.9	0.362
14-15	9/16"	14.2	57.2	31.8	33.2	34.0	23.9	52.3	63.5	0.494
16	5/8"	14.2	57.2	31.8	33.2	34.0	23.9	52.3	63.5	0.498
18-20	3/4"	15.8	69.9	36.6	38.1	35.3	26.9	57.2	72.1	0.644
22	7/8"	19.0	79.2	41.1	44.4	40.1	31.8	62.0	80.2	0.961
24-26	1"	19.0	88.9	46.0	47.8	45.0	31.8	66.8	88.1	1.140
28-30	1-1/8"	19.0	98.6	50.8	50.8	48.5	31.8	71.4	91.2	1.280
32-34	1-1/4"	22.4	113.0	56.4	58.7	55.1	36.6	79.5	105.0	1.980
36	1-3/8"	22.4	113.0	60.5	60.5	58.7	36.6	79.5	106.0	2.000
38	1-1/2"	22.4	126.0	60.5	65.8	62.0	36.6	86.6	113.0	2.460
40-42	1-5/8"	25.4	135.0	66.5	69.9	67.6	41.4	92.2	121.0	3.190
44-46	1-3/4"	28.7	146.0	69.9	77.7	74.2	46.0	96.8	133.0	4.230
48-52	2"	31.8	164.0	76.2	85.9	83.3	50.8	113.0	149.0	5.890
54-58	2-1/4"	31.8	181.0	81.0	98.6	81.0	50.8	116.0	162.0	7.250
62-64	2-1/2"	31.8	195.0	87.4	105.0	93.7	50.8	103.0	168.0	8.610
68-72	2-3/4"	31.8	211.0	90.4	111.0	124.0	50.8	127.0	175.0	10.430
75-78	3"	38.1	233.0	98.6	120.0	113.0	60.5	135.0	193.0	14.060

All dimension and weight are approximate.



HG-3450

Distributor

www.besteel.biz
inquiry@besteel.biz